
dynaudioacoustics

M2 MkII





Extremely accurate, remarkably compact

More SPL, more accuracy and more finesse – across the board.

The concept for the original M2 was a compact three-way near-/mid-field monitor designed to produce maximum accuracy and SPL in a compact enclosure.

This second generation takes that idea and supercharges it. The M2 MkII uses our latest Esotar3 soft-dome tweeters, plus our newest MSP (Magnesium Silicate Polymer) midrange and low-frequency drive units. Inside there's a custom hand-built crossover. And together, they deliver astonishingly accurate imaging and frequency response. Exactly what you need in your studio.

The new M2 MkII goes far beyond the SPL and frequency range of the original version. It's a generational step in our obsessive pursuit of professional monitoring excellence.

Application	M2 MkII Music and post-production
Type	3-way hybrid
Frequency response	40Hz – 20kHz
Maximum SPL at 2 metre	125dB stereo
Crossover frequencies	700Hz and 3700Hz
Total harmonic distortion	1% at 90dB
Recommended amplifier power	Two channels: 250-500W/channel per speaker
Cabinet dimensions (H x W x D)	350 x 680 x 500mm
Weight	35kg
Finish	Black textured paint
Drivers	
High frequency	Esotar3
Midrange	75mm soft-dome
Low frequency	24cm MSP x2
Amplifier recommendation	
Dynaudio Acoustics	DA20 (with filters), DA40, DCA800 (with filters)
Options	
Hardwood cabinet	Oak, cherry, walnut, maple
Custom cabinet sizes	On request

dynaudioacoustics M2 MkII

All systems are made to order.
Price and delivery on application.

Learn more, read our reviews and find your nearest Dynaudio dealer at
dynaudio.com and **facebook.com/dynaudiogroup**

Dynaudio A/S

8660 Skanderborg, Denmark

Product Insert, M2 MkII. Item no. 45538233

All text and image copyrights reserved.

Subject to change without notice.